

FLOORPAN CLASSIC **FPC009** - LEFKAS



FLOORPAN CLASSIC **FPC094** - SUNNY OAK



FLOORPAN CLASSIC **FPC093** - SAVANI OAK



FLOORPAN CLASSIC **FPC052** - LIMA



FLOORPAN CLASSIC **FPC006** - STORK



FLOORPAN CLASSIC **FPC062** - ATLAS



FLOORPAN CLASSIC **FPC092** - GRISTA OAK

15 YEARS
DOMESTIC USE
GUARANTEE

32

AC4

10 YEARS
COMMERCIAL USE
GUARANTEE

BLUE ANGEL
THE GERMAN ECOLABEL

24 HRS WATER-RESISTANT - NALFA SURFACE SWELL TEST
24 HOURS

CLASSIC
SPEC SHEET

FLOORPAN CLASSIC

THICKNESS	mm	8	EN 13329 + A1
WIDTH	mm	197	EN 13329 + A1
LENGTH	mm	1205	EN 13329 + A1
SURFACE		Timberland	
EUROPEAN STANDARD	-	15 YEARS DOMESTIC USE GUARANTEE 32 AC4 10 YEARS COMMERCIAL USE GUARANTEE	EN 13329

PACKAGE DETAILS	
PIECE	8 piece / 1 package
M2	1,899 m2
KG	14 kg

PALLET DETAILS	
PIECE	60 boxes / 1 pallet
M2	113,94 m2
KG	840 kg

CLASS		-	32	EN 13329+A1
ABRASION RESISTANCE		-	AC4	EN 13329+A1
THICKNESS SWELLING		%	≤18	ISO 24336
RESISTANCE TO IMPACT	SMALL BALL	N	≥12	EN 13329+A1
	LARGE BALL	mm	≥750	EN 13329+A1
WARRANTY DOMESTIC / COMMERCIAL		Years	15/10	-
RESISTANCE TO STAINING		-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438
SURFACE SOUNDNESS		N/mm²	≥1.25	EN 13329+A1
LOCK STRENGTH	LENGTH	kN/m	fl0,2 ≥ 1	ISO 24334
	WIDTH	kN/m	fs0,2 ≥2	
EFFECT OF CASTOR CHAIR		"25.000 Cycles"	No Damage	EN 425:2002b
EFFECT OF A FURNITURE LEG		-	No damage shall be visible when tested with foot type 0	EN 424
OPENING BETWEEN ELEMENTS. (0)		mm	"0 average ≤ 0,15 mm 0 max. ≤ 0,20 mm"	EN 13329+A1
HEIGHT DIFFERENCE BETWEEN ELEMENTS (H)		mm	h average ≤ 0,10 mm h max. ≤ 0,15 mm	EN 13329+A1
MOISTURE CONTENT		%	4-10	EN 322
FIRE RESISTANCE		Class	CflS1	EN 9239-1
FORMALDEHYDE RELEASE		mg/m²h	≤3,5 (E1)	EN 12460-3

CLASSIC
8MM- CLASS 32- AC4

FAST AND EASY ASSEMBLY · SUITABLE FOR UNDERFLOOR HEATING · RESISTANT TO UV RAYS · RESISTANT TO POINT STRIKES · ENVIRONMENTALLY FRIENDLY · BASE PANEL, HIGH DENSITY FIBERBOARD · RESISTANT TO CIGARETTE FIRE · RESISTANT TO SCRATCH · EASILY CLEAN AND MAINTAINED, HYGIENIC · NOT AFFECTED BY STAINS · RESISTANT TO FURNITURE WHEEL ABRASION · E1 GRADE