VIBRANCE

MADE IN BELGIUM BY PERGO

WIDE
HYDRO



LATTE OAK



CHAI LATTE OAK



WILDFLOWER OAK



SUNSET ROAST OAK



GARDA OAK



SUNKISSED OAK

EN ISO 10874

panoramic DESIGN

Water 48Hr Resistant

Residential 25 Years Warranty

Commercial 10 Years Warranty

Expansion Parameters 13 x 13

VIBRANCE

TECHNICAL SPECIFICATIONS

HDF 8 mm | 1261 x 244 mm | 8 planks/pack | ± 15,5 kg/pack | 2.4615 m² / pack

	Method	Parameters	Norm Requirements	Values
Abrasion resistance	ISO24338 - Procedure A		≥ 4000 cycles	≥ 4000 cycles
Abrasion class	EN 13329		AC4	AC4
Impact resistance	EN 17368	Small ball	≥ 35mm	≥ 35mm
	EN 13329	Big ball	≥ 600mm	≥ 600mm
Scratch resistance	EN 438-2, 25		Charge ≥ 3N	Charge ≥ 3N
Effect of a castor chair	ISO 4918 (with underlay)	Type W (EN 12529)	15000 cycles	No change
Thickness swelling	ISO 24336	After 24h at 20°C	≤ 18%	≤ 18%
Locking strength	ISO 24334	Fl0,2 long side	≥ 1 kN/m	≥ 1 kN/m
		Fmax long side		≥ 1 kN/m
		Fs0,2 short side	≥ 2 kN/m	≥ 2 kN/m
		Fmax short side		≥ 2 kN/m
Effect of a furniture leg	EN 424		No damage (type 0)	No visible damage
Resistance to staining	EN 438	Group 1,2	Class 5	Class 5
	EN ISO 4892	Group 3	Class 4	Class 4
Light fastness	2:2006/A1:2009 Pro. B - Cycle 5	Grey reference	Class ≥ 4	Class 4
Formaldehyde emission	EN 717-1	ppm	E1	< 0,5
Anti-static	EN 1815		≤ 2,0 kV	≤ 2,0 kV
Reaction to fire	EN 13501-1	Class		Cfl-s1
Thermal resistance	EN 12667	m²K/W		0,055 m²K/W
Slip resistance	EN 13893	μ	μ ≥ 0,30	DS: μ ≥ 0,30



VIBRANCE WIDE HYDRO